

Exceptional Design

- Certified to haul up to 67,000 lbs.
- Watertight container
- Suited for municipal waste including sludges, hazardous waste and other solids

Safety & Quality

- Dump door has four ratchets to safety
- Tank goes through a 100+ point safety checklist

Cost Savings

- Smooth wall interior for easy clean-out



SPECIFICATIONS

Weights & Measures	IM-240	Tests Performed	Std	Warranty	Std
Tank length	20 - 0"			1-year structural	•
Tank width (outside)	8' - 0" (outside) 7' - 6" (inside)			6-months coating	•
Tank height (grade to roof deck)	6' - 6"				
Weight (lbs)	29,950				
Capacity (BBLs/Gals)	27.6 cu. yd.				

OPTIONS & FEATURES:IM-240

TANK OPTIONS	Qty	Std	Opt
--------------	-----	-----	-----

DESIGN FEATURES			
Liner hooks inside of box	4	0	
Structure to support the addition of 2 placards on each side of container	1	0	
Tested and Certified to 67,000# gross weight	1	0	
Fork pockets: minimum opening size 14 1/2" x 5"	1	0	
	1	0	
	1	0	
	1	0	

ADDITIONAL SAFETY FEATURES			
	1	0	
	1	0	

STRUCTURAL DESIGN			
Floor: 1/4" thick ASTMA36 carbon steel 3 gauge, 20 ft. ISO Skids	1	0	
Sides: 7 gauge steel plate	1	0	
Bulkhead: 7 gauge steel plate	1	0	
Door: 1/4" plate / Dump door with (4) ratchets	1	0	

DESIGN FEATURES			
-----------------	--	--	--

PAINT SPECIFICATIONS			
Interior blast: SSPC-SP-10/Near White			0
Interior coating: Carboline Phenoline 310 (100% solids)/high performance Epoxy coating 20-30 Mils D.F.T.			0
Exterior blast: SSPC-SP-6/Commercial	1	0	
Exterior coating: Per customer specifications	1	0	

OPTIONS			
Tarps			0
J Hooks			0
Bracing gussets (ISO blocks)			0
Interior dirt shedders			0
Tarp rod supports			0
Deflectvtor Plate under splash guard			0
3" x 86 1/2" structural „C“ channel to floor			0

