

## Available Models

- Model OTRC-20 20 cu. yds.
- Model OTRC-25 25 cu. yds.
- Model OTRC-30 30 cu. yds.
- Model OTRC-40 40 cu. yds.

## Exceptional Design

Open top design with tapered side walls for easy loading and unloading



## Safety & Quality

- Both horizontal and vertical supports for strength
- Tank goes through a 100+point safety checklist

## Cost Savings

- Smooth interior walls save time for cleaning, reduces costs and increases tank life



Sabre's Open Top Refuse Containers are available in four standard sizes and can be used for many applications. These tanks are watertight containers that can be filled and used to temporarily store a variety of liquid or solid materials.

These tanks are ideal for:

- Environmental cleanup projects
- Municipal refuse, recycling and compost
- Construction projects
- Industrial applications

Please give us a call to learn more about these tanks and our other products.

# SPECIFICATIONS

Weights & Measures	OTRC-20	OTRC-25	OTRC-30	OTRC-40
Capacity (Cubic Yards)	20	25	30	40
Tank Wall Height (grade to top)	42"	52"	62"	82"
Tank Length	22' - 10"	22' - 10"	22' - 10"	22' - 10"
Tank Width (tapered 3" per side)	6' - 9 1/4" to 7' - 3 3/8"	6' - 9 1/4" to 7' - 3 3/8"	6' - 9 1/4" to 7' - 3 3/8"	6' - 9 1/4" to 7' - 3 3/8"
Tank Weight (lbs)	5,400	6,060	6,310	7,170

## OPTIONS & FEATURES

TANK OPTIONS	Qty	Std	Opt
<b>DESIGN FEATURES</b>			
Dirt shedder and backup plate	1	●	
Front nose rollers: 4" OD x 6"	2	●	
Side swing tailgate with seal	1	●	
1" adjustable door hinge pins	2	●	
Front Hook: 1 1/4" plate	1	●	
Door chain tie-off	1	●	
Tarp Hooks	20	●	
Tarps	1		●
Rear wheels: 8 5/8" diameter x 6"	2	●	

DESIGN FEATURES	Qty	Std	Opt
<b>STRUCTURAL DESIGN</b>			
Floor: 3/16" thick ASTM A36 carbon steel	1	●	
Understructure: 1/4" x 2" x 6" tubing @ 36" ID	1	●	
Sides/ends: 3/16" thick ASTM A36 carbon steel	1	●	
Top: 3/16" x 3" x 4" ASTM A36 tube	1	●	
<b>PAINT SPECIFICATIONS</b>			
Interior blast: SSPC-SP-10/Near White	1		●
Undercoating: Water base asphalt emulsion	1	●	
Exterior blast: SSPC-SP-6/Commercial	1	●	
Exterior coating: Carboline Carbothane 8812/8845 DTM High Gloss Polyurethane 3-5 Mills D.F.T.	1	●	

